



53 Ubi Avenue 1 #03-42  
 Paya Ubi Industrial Park  
 Singapore 408934  
 Tel: 6749 3003 Fax: 6742 3003



新加坡水处理协会  
 Ordinary Member

www.hitechaem.com  
 contact@hitechaem.com  
 ROC No: 199205407G  
 GST No.M2-0109882-3



**WB-80CH**  
**HOT & COLD**  
**INSTANT WATER**  
**BOILER**

挂墙即热式开水机



Made in Taiwan  
 台湾制造

產品並榮獲經濟部標準檢驗局  
 正字標記、ISO9001品保認證



即熱式開水機	ESPERO™ WB-80CH (Hot and Cold only)
Type	Wall mount or Table Top (Dual Position)
External Filter	Hy-Q. 1-Stage Water Filtration System
Casing	SUS304 Stainless steel, satin finish
Dimensions	W440 x D330 x H820 mm
Capacity:	Capacity 20L; running 30 litres per hour (Hot) and 15 litres per hour (Cold)
Water Drip Tray	Attached ABS and Stainless Steel tray
Water Temperature	Hot :100°C (±98°C) Cold : 4 to 8 °C
Faucet (Hot and Cold)	Tomlinson No-Drip faucets. Made in USA ~Red and Black color ~Polypropylene ~Stainless steel & Copper
Thermostat	EGO Germany, Hot water temperature adjustable, automatic thermostat regulates temperature to within safe limits
Functions	<ul style="list-style-type: none"> <li>The water temperature keeps up to 98°-100°C</li> <li>Overload Relay cuts off electrical power if temperature rises to an unsafe level</li> <li>Withstand feed water pressure up 1-3 kg / cm</li> </ul>
Power Consumption	Up to 2400W
Power Supply	50Hz
Electrical Supply	220V / 13 amps
Heating System	Stainless Steel Heating element
Supply Inlet	½ inch diameter
Installation	½ inch diameter

Specifications & designs subject to changes without notice.



torayvino. RUHENS





53 Ubi Avenue 1 #03-42  
 Paya Ubi Industrial Park  
 Singapore 408934  
 Tel: 6749 3003 Fax: 6742 3003



新加坡水处理协会  
 Ordinary Member


www.hitechaem.com  
 contact@hitechaem.com  
 ROC No: 199205407G  
 GST No.M2-0109882-3

## Hy-Q™ Water Filtration System 물 여과 체계 净水过滤系统



An **Economical & Eco-friendly** 实惠又環保 Filtration System. Filtering sediments and impurities while preserving elements and essential minerals for our bodies. 保留礦物質微量元素

- ✓ Periodic Filter replacements required subject to usage/environment/infrastructure
- ✓ Filters should be change when the flow becomes small, the unpleasant taste, or the odor in the water



WATER PURIFIER QUALITY EXAMINATION CERTIFICATE (Korean Water Purifier Industry Cooperation)



WQA (Water Quality Association)



ISO 9001 CERTIFICATE

### Single Stage Filtration

1개의 단계 Hy-Q™ 물 여과 체계  
 NSF의 물滤芯  
 Sediment 沉积物



Brand	<b>Hy-Q™ 물AQUA</b>
Type	<b>Sediment Filter 沉积物</b>
Dimension	12" x 2½"
Maximum Flow	1.0 GPM
Maximum Pressure	125 PSI
Maximum Temperature	120° F
Service Life	2500 Gallons (9400 litres)
Function	<b>Hy-Q Sediment filter</b> removes dirt, other minute impurities, particles that are 15 times of a grain of sand and various foreign bodies that come from the services water pipe such as bits of rust.
Made In Korea	한국에서 만드는 韩国制造

**Caution:** Use only with municipally –treated or microbiologically water. Do not use with water of unknown source or quality.



torayvino. RUHENS



Disclaimer: The product information is meant for general information purposes only and shall not be construed as implying any warranty relating to accuracy of the information, fitness for purpose or performance. Hi-Tech (AEM) Pte Ltd hereby disclaims all liability with respect to any errors or omissions in the information.